

Honeywell Xenon Ultra 1960g/h & 1962g/h Barcode Scanners for Retail and Healthcare

Accessories Guide

Contact **mobit** for more info:

- DE/EN/IT: **+41 (0)44 800 16 30**, CH-8306 Brüttisellen
- FR: **+41 (0)21 651 98 98**, CH-1020 Renens
- E-mail: info@mobit.ch
- Contact form on www.mobit.ch



Access Points, Charge Cradles and Communication Cradles



AP-010BT-07N

Bluetooth Access Point
Access point for scanners.
Class 2 Bluetooth, 10m (33'), RS232/USB/KBW/IBM (cable sold separately).



AP-010BT-HC

Bluetooth Access Point - Healthcare
Access point for scanners.
Class 2 Bluetooth, 10m (33'), RS232/USB/KBW/IBM (cable sold separately).



CCB-U00-H-KIT
Contactless:
CCB-U00-H-WCKIT

Xenon Ultra Charge and Communication Vertical Base Kit - Healthcare
Presentation charge and communication base, Class 1100M / Class 2 10M Bluetooth, 7 scanners can be connected, RS232/USB/KBW host interfaces (cables sold separately), white, disinfectant ready anti-microbial housing.
Enable Charge only mode: BASLNKO.



CCB-U00-G-KIT
Contactless:
CCB-U00-G-WCKIT

Xenon Ultra Charge and Communication Vertical Base Kit - General Purpose
Presentation charge and communication base, Class 1100M / Class 2 10M Bluetooth, 7 scanners can be connected, RS232/USB/KBW host interfaces (cables sold separately), black, disinfectant ready housing.
Enable Charge only mode: BASLNKO.



General Purpose (Black)
Battery Cup:
1962G-BAT-CUP
Contactless Cup:
1962G-WC-CUP
Healthcare (White)
Battery Cup:
1962H-BAT-CUP
Contactless Cup:
1962H-WC-CUP

Xenon™ Ultra Charge and Communication Presentation Cup Only
1962 Charge and Communication Cup for use with universal presentation base.



General Purpose (Black):
CCB-U00-G
Healthcare (White):
CCB-U00-H

Xenon Ultra Charge and Communication Presentation Universal Base Only
1962 Charge and Communication universal base for use charging cup of presentation CCB.



CCB-ULTRA-HORIZ-HC
Contactless Version:
CCB-ULTRA-HORIZ-HCWC

Xenon Ultra Charge and Communication Horizontal Presentation Base - Healthcare
Desktop/Wall mount charge and communication base, class 1100M/class 2 10M Bluetooth®, white, disinfectant ready anti-microbial housing.



CCB-ULTRA-HORIZ-GP
CCB-ULTRA-HORIZ-GPWC

Xenon Ultra Charge and Communication Horizontal Presentation Base - General Purpose
Desktop/Wall mount charge and communication base, class 1100M/class 2 10M Bluetooth, black, disinfectant ready housing.

Power Options and Power Supplies



BAT-SCN11

Lithium-ion Battery

Smart battery: Lithium-ion battery for Xenon™ Ultra 1962 Bluetooth® scanners.



Black: BAT-SCN11WC
White: BAT-SCN11WCHC

Lithium-Ion Battery – Contactless

Smart battery: Lithium-ion battery for Xenon Ultra 1962 contactless Bluetooth scanners.



SUPCAP-SCN11

Battery-Free Supercapacitor

Battery-free super capacitor for Xenon Ultra 1962 battery-free Bluetooth scanners.



Black: SUPCAP-SCN11WC
White: SUPCAP-SCN11WCHC

Battery-Free Supercapacitor – Contactless

Battery-free Super capacitor for Xenon Ultra 1962 battery-free contactless Bluetooth scanners.

For Xenon Ultra 1960 Corded Scanner ONLY



46-00525-6

Power Supply – NA Plug

Power Supply: NA plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz.



46-00526

Power Supply – EU Plug

Power Supply: EU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz.



46-00528

Power Supply – AU Plug

Power Supply: AU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz.



46-00529

Power Supply – CN Plug

Power Supply: CN plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz.

For Xenon Ultra 1962 Cordless Scanner ONLY



46-00535-6

Power Supply -NA Plug

Power Supply: NA plug, 3.0A @ 5V DC, 100-240V AC @ 50-60Hz.



46-00536-6

Power Supply – EU Plug

Power Supply: EU plug, 3.0A @ 5V DC, 100-240V AC @ 50-60Hz.



46-00537-6

Power Supply – AU Plug

Power Supply: AU plug, 3.0A @ 5V DC, 100-240V AC @ 50-60Hz.



46-00538-6

Power Supply – CN Plug

Power Supply: CN plug, 3.0A @ 5V DC, 100-240V AC @ 50-60Hz.

Presentation Stands



STND-22F00-016-6

Xenon™ Ultra 1960 Stand – Flexible Presentation Stand

Stand: gray, 22cm (9 in) height, flexible rod, large oval weighted base, Xenon Ultra 1960 cup.



STND-22F00-001-6

Xenon XP 1950 Stand – Flexible Presentation Stand

Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon 1900/1950 cup.

Use **PAPTPR** to configure your Xenon Ultra 1960 to utilize this legacy stand for presentation mode scanning.



Contact **mobit** for more info:

- DE/EN/IT: **+41 (0)44 800 16 30**, CH-8306 Brüttisellen
- FR: **+41 (0)21 651 98 98**, CH-1020 Renens
- E-mail: info@mobit.ch
- Contact form on www.mobit.ch

Cables

CBL-020-300-C00

RS-232 Power Cable

Cable: RS232(5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9, w/o ferrite.

*1960 Corded Only.

CBL-120-300-C00

RS-232 Power Cable

Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.

*1960 Corded Only.

CBL-220-300-C00

RS-232 Power Cable

Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle™.

*1960 Corded Only.

CBL-420-300-C00

RS-232 Power Cable

Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).

*1960 Corded Only.

CBL-MAG-300-S00

RS-232 Power Cable

Cable: RS-232 (5V signals), Magellan™ Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.

*1960 Corded Only.

CBL-500-500-C00

USB Power Cable

Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power, w/o ferrite.

CBL-500-500-S00

USB Power Cable

Cable: USB, black, Type A, 5m (16.4'), straight, 5V host power, w/o ferrite.

CBL-500-400-C00-01

USB Power Cable

Cable: USB, black, Type A, 4m (13.1'), coiled, 5V host power, w/o ferrite.

CBL-500-150-S00

USB Power Cable

Cable: USB, black Type A, 1.5m (5'), straight, 5V host power, w/o ferrite.

CBL-500-300-C00

USB Power Cable

Cable: USB, black, Type A, 3m (9.8ft), coiled, 5V host power.

CBL-500-300-S00

USB Power Cable

Cable: USB, black, Type A, 3 m (9.8'), straight, 5V host power.

*Cable shipped with Xenon Ultra 1960 kit SKUs.

3012-6337-001

USB Power Cable

Cable: USB, Type A, 2.7M (8.8'), straight, 5V host power.

*Cable shipped with Xenon Ultra 1962 Kit SKUs.

CBL-720-300-C00

Keyboard Wedge Power Cable

Cable: KBW, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power, w/o ferrite.

* 1960 Corded Only.

CBL-800-300-C00

USB Power Cable, Type C

Cable: USB Type C, black, 3m (9.8'), coiled, 5V host power, w/o ferrite.

CBL-500-120-S00-HS

USB Power Cable, High Speed

Cable: USB, Type A, black, 1.2m (3.9'), 5V host power, w/o ferrite.

CBL-720-300-C00-01

Keyboard Wedge Power Cable

Cable: KBW, black, PS2, 3 m (9.8 ft), coiled, 5V external power with option for host power.

*1962 Cordless only.

CBL-020-300-C00-03

RS-232 Power Cable

Cable: RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.

*1962 Cordless only.



Honeywell Xenon Ultra 1960g/h & 1962g/h Barcode Scanners for Retail and Healthcare

Accessories Guide

Contact **mobit** for more info:

- DE/EN/IT: **+41 (0)44 800 16 30**, CH-8306 Brüttisellen
- FR: **+41 (0)21 651 98 98**, CH-1020 Renens
- E-mail: info@mobit.ch
- Contact form on www.mobit.ch

